

OSU STANDARD HOLOPHANE LIGHTING FIXTURES

Poles:

Post Top Sitelink Pedestrian – North Yorkshire (NY), Aluminum (A), Height (14’), Shaft Size (L5J), Base Diameter – 17”, Tenon Size (3”x3”-PO7), Pole Mounting Options (ABG), Color (Bronze)

#: NY A 14 L5J 17 PO7 ABG BZ

Parking Lot Fluted – North Yorkshire (NY), Material- Steel (S), Height (21’), Shaft Style (FTB), Base-17”, Tenon P10 (3”x9”), Mounting-ABG, Finish-Bronze (BZ); Poles may also be Aluminum – No clamshell base (Parking Lots)

#: NYS 21 FTB 17 P10 ABG BZ

Roadway Fluted – North Yorkshire (NY), Material-Steel (S), Height (21’-4”), Shaft Style Round Tapered Fluted (12 Flat), Tenon (4.5” x 10”), (4) Banner Arm Provisions, Mounting 10.4” Butt Diameter Baseplate – 15” bolt circle, Color Dark Bronze (DB); Clamshell Base (CSB-24” Diameter, 42” Tall); CIS- Cast Iron Steel

#: FL210-T40B210-4.5T10-BZ-(4)BAPADS - NY24CSBCIDBH (Modified 3/2/2017)

Mounting Arms:

Parking Lot Single Arm – West Liberty (WLC), 72”, Cast Aluminum (CA), Color Dark Bronze (DBH), Swivel-Dark Bronze (DBZ)

#: WLC72/1 CA DBH *WEST LIBERTY FITTER TO BE ORDERED WITH LUMINAIRE

Parking Lot Double Arm – West Liberty (WLC), 144”, Cast Aluminum (CA), Color Dark Bronze (DBH), Swivel-Dark Bronze (DBZ)

#: WLC144/2 CA DBH *WEST LIBERTY FITTER TO BE ORDERED WITH LUMINAIRE

Roadway Arms Single – **#:ATC51/1 CA DBH**

Roadway Arms Double – **#:ATC102/2 CA DBH**

Luminaires:

Post Top LED – Utility Post top LED (PTUE), Wattage 100W, Color Temp 4K,

Voltage 120/277 (AS), Optics- Asymmetric glass refractor (GY3), Color-Bronze (BZ), Finial-Spike (S), Option-ADJUSTABLE OUTPUT (AO)

#: PTUE2 P30 40K AS GL3 BZ S AO

Roadway – Esplanade LED (ESL), Wattage 118W, Color Temp 4K, Voltage 120-277-AS or 347-480-AH, Top Entry- Stem Mount (S), Housing Color – Bronze (BZ), Optics-Teardrop Asymmetric (3), Adjustable Output (AO), Short Skirt (SS); with bronze Boston Harbor Fitter (BLDF13200 BZ) (? = Voltage Either AS or AH)

Roadway #: ESL2 P30S 40K ? BZ TG 3 S AO SS BHDF13 200 BZ

Parking Lot - Esplanade LED (ESL), Wattage 118W, Color Temp 4K, Voltage 120-277-AS or 347-480-AH, Top Entry- Stem Mount (S), Housing Color – Bronze (BZ), Optics-Teardrop Asymmetric (3), Adjustable Output (AO), Short Skirt (SS); with bronze West Liberty Fitter (WLD13 200 BZ) (? = Voltage Either AS or AH)

Parking: # ESL2 P30S 40K ? BZ TG 3 S AO SS WLDF13 200 BZ

Bollard Lights:

Bollard with Convenience Outlet - BOLLARD SHAFT Columbia Lighted Bollard (BOLC), 3'-8" Height, 13" Diameter Base, Internal Light And White Lens, Cast Aluminum, Dark Bronze, INCANDESCENT, MEDIUM BASE SOCKET, 120 Volt, RECEPTACLE PROVISION GFI RECEPTACLE WITH WEATHERPROOF WHILE CLOSED COVER. HOLOPHANE BRONZE 3/4"X18" ANCHOR BOLTS INCLUDED

BOLC4413LWCADBHINC120-RXXXY FG-SDBH AB-31-4 RFD267273

Options:

Banner Arms – *BA30 BO H 4 BZ* (Banner Arm 30", Bolt On, Finial-Half Sphere (H), 1" diameter (4), Bronze (BZ))

Contractor Installed in Base:

Slow-Blow In-line fuses

All post top lights and bollard lights are typically 120V. All parking lot and roadway lights are typically 480V single phase.